

CALYPSO 2G.SH

N2/Air Gas Generator LCMS for Shimadzu

Reference : CALYPSO.2G/1.SH (With compressor)
CALYPSO.2G/1.HF.SH (With compressor)



Description

The CALYPSO.2G/1.SH is a dual flow generator, which has been specifically designed to meet the nitrogen and dry air needs to supply the Shimadzu LCMS 8045, 8050, 8060 which allows users to change the flow ratio of nitrogen and dry air from the touch screen display, such that the total flow is 25 L/min, split between nitrogen and dry air.

The CALYPSO.2G/1.HF.SH has been designed to provide increased flows of Nitrogen and Dry Air for the latest Shimadzu LCMS-9030, or when LCMS 8045, 8050, 8060 are operated in High Flow gas delivery mode.

The generator is built with internal air compressors as standard, and is extremely quiet in operation.

The generator is controlled using the latest in color touch screen technology to display the process in real time, inlet / outlet pressure, N2/Air Flow and status of the system with remote access for diagnostic control.



UNIQUE AND INTELLIGENT OPERATOR
INTERFACE WITH REMOTE ACCESS

Applications

LCMS-8045

LCMS-8050

LCMS-8060

LCMS-9030

Benefits & Savings

INCREASED LABORATORY EFFICIENCY

A constant, uninterrupted gas supply of guaranteed purity eliminates interruptions of analyses to change cylinders and reduces the amount of instrument re-calibrations required.

IMPROVED ECONOMY

Clean dry air and nitrogen gas produced as standard.

IMPROVED SAFETY

Clean dry air and nitrogen gas produced at low pressure and ambient temperature removes the need for high pressure cylinders.

SECURITY OF SUPPLY

Integral oil free air compressor as an option guarantees continuous gas supply, independent of in house compressed air supply.

SIMPLE INSTALLATION

Gas generators can be installed in the laboratory, on or under a bench, eliminating the need for long gas lines from cylinders secured elsewhere.

Standard Features

- Intelligent color touch screen to provide simple and user friendly management of all functions of the unit
- Fully regenerative PSA technology
- Complete 'Plug and Play' system specifically designed for the Shimadzu LCMS-8045, 8050, 8060, 9030
- High Nitrogen pressure up to 6.9 bar (100 psi)
- With integral oil free air compressor
- Quiet thanks to the Soundproofed compressor box and anti-vibration features
- Auto start
- Audible alarm display and Visual maintenance indication with history log
- Outlet flow indicator
- Energy Saving Technology (EST) :
 - Switch off the compressor when gas supply is not required
 - Allowing low energy consumption and increasing durability of the compressor
- Remote PC monitoring and diagnostic analysis via USB to interface the unit with customer's PC software (allow to carry out checks and maintenance effectively, only via a remote connection)
- Compact design
- Fit with wheels

N2
AIR

MODELS	CALYPSO.2G/1.SH	CALYPSO.2G/1.HF.SH
GENERALS INFORMATIONS		
Max Outlet Flow rate	Max Flow Rate up to 25 L/min of Air & Nitrogen combined	Up to 27 L/min N2 29 L/min Air
Max Nitrogen pressure	6.9 bar (100 psi)	
Purity Air/N2	Air Dew point -20°C (-4°F) ; Nitrogen < 2% O2	
Particles	< 1 μ	
Touch screen	Touch screen (operating parameters, system status, alarms and maintenance)	
Max Relative Humidity	80% RH @ 25°C (77°F)	
Temperature range	From 5 - 25°C (41 - 77°F)	
Max Altitude	3000 Meters	
Noise level @ 1M	52 dB (A)	53 dB (A)
Dimensions (W x H x D)	47.5 x 66.2 x 79 cm (18.7" x 26" x 31")	47.5 x 100 x 79 cm (18.7" x 39" x 31")
Weight (kg/lbs)	120 / 264.5	155 / 341
Electrical supply	220 - 240 V ac / 1 ph / 50 - 60 Hz	
	110 - 120 V ac / 1 ph / 50 - 60 Hz	
Power consupption	1 700 VA	2550 VA
Fuse	10A	
CONNECTIONS		
Nitrogen/Air outlet	2 x 1/4"G (BSP) Female	
COMMUNICATION		
USB/PC Control	In series	

GoldService
 — Satisfaction Guaranteed —

The products are guaranteed 24 months*. Beyond, your investment continues to be supported by our maintenance program **[Gold Service]**. Our world class technical assistance offers Programmed preventive maintenance to ensure optimal performance of your Gas generator F-DGSi and a priority intervention in case of failure.

*Year 2 of warranty subject to generator being serviced at end of the first year by a F-DGSi-approved agent in accordance with fixed annual maintenance schedule. For full terms and conditions, visit www.f-dgs.com

GS: TECNOLOGIA APLICADA 

Certified Product

