

CRYOGEN

Liquid Nitrogen Generator

Reference : CRYOGEN.[Flow rate]



Description

The CRYOGEN is a range of stand-alone Liquid Nitrogen Generators.

Utilising a reliable 'Cryo-refrigerator' design of cold head technology and helium compressor, the nitrogen gas is then produced using the PSA technology which is cooled to 77K (-196°C) to produce liquid nitrogen.

The Generators are controlled using the latest in HMI touch screen technology to display the process in real-time, showing the liquid level of the dewar, PSA nitrogen production giving a fully automated system at the touch of a button with remote access for diagnostic control.



UNIQUE AND INTELLIGENT OPERATOR INTERFACE WITH REMOTE ACCESS

Applications

IVF (storage of samples)

Cryotherapy

Dermatology

Lab applications

Metal treatment

Benefits & Savings

CryoGen Generation Plants is your reliable and efficient alternative to conventional Liquid Nitrogen supplies. Taking away the on-going costs, safety considerations of deliveries, transportation of traditional liquid gas supplies.

Your on-site Liquid Nitrogen systems will be some of the most advanced and intelligent available.

The control system gives the user all the information necessary to ensure an efficient and consistent supply of Liquid Nitrogen and nitrogen gas are always available. From the process to flow and alarms, including automatic operation, Trend graphs, service alarm and service records page, there is simply no other Liquid Nitrogen System.

Standard Features

- Different flow rates
- Turnkey solution
- Compact and Quiet design
- Built in Nitrogen PSA with oil free air compressor
- Automatic operation
- Energy saving mode
- LN2 Dewar Liquid Level
- Vacuum prevention system on liquid dewar
- Built in O2 analyser with alarm
- Alarms with help menu
- Remote PC monitoring and diagnostic analysis via USB/RS232 to interface the unit with customer's PC software (allow to carry out checks and maintenance effectively, only via a remote connection)
- Option : Fitted with medical filter
- Wheels for easy installation

LIQUID
N2

MODELS	CRYOGEN.10	CRYOGEN.20	CRYOGEN.30	CRYOGEN.40	CRYOGEN.60
GENERALS INFORMATIONS					
Max L/Day	10	20	30	40	60
Max L/Hour	0.42	0.83	1.25	1.70	2.50
Dewar Capacity (L)	35	100		160	210
N2 Gas (L/min)	5.5	11	13	20	33
Cooling Water (L/min @ 27°C)	2.8	4.5	6.0	6.0	7.6
Temperature range	7 - 38°C (45 - 100°F)				
Dimensions (W x H x D)	120 x 180 x 60 cm (47" x 71" x 24")				
Weight (kg/lbs)	150 / 330	200 / 441	300 / 661	320 / 705	350 / 771
Electrical supply	220 - 240 V ac / 1 ph / 50 - 60 Hz				
	110 - 120 V ac / 1 ph / 50 - 60 Hz				
Power consumption (Kw)	2.2	3.4		5.5	7.5
CONNECTIONS					
Inlet/outlet	G 3/8				
COMMUNICATION					
USB/PC Control	In series				

GoldService
 — Satisfaction Guaranteed —

The products are guaranteed 24 months*. Beyond, your investment continues to be supported by our maintenance program **[Gold Service]**. Our world class technical assistance offers Programmed preventive maintenance to ensure optimal performance of your Gas generator F-DGSi and a priority intervention in case of failure.

*Year 2 of warranty subject to generator being serviced at end of the first year by a F-DGSi-approved agent in accordance with fixed annual maintenance schedule. For full terms and conditions, visit www.f-dgs.com

GS: **TECNOLOGIA APLICADA** 

Certified Product

